dAGE415U20-PM

4U 15-bay SATA eSATA Port Multiplier JBOD Chassis 750W PSU



Specifications

Dimension (W x H x D)	19 x 7 x 20 inches
Cooling	1 x 120mm Cooling Fan
HDD Interface	SATA I/II
Host Interface	3 eSATA Connectors (Port Multiplier)
LED Display	LED for Power On/Off, HDD
Hot-Swap	Both on Host and Device
Material	Chassis: 1.2 mm SECC Zinc-Coated Steel
Power Supply	750W single psu (with 400W redundant psu model: dAge415U20-PM-R)

Features

- Supports SATA I/II (1.5/3 Gbps)
- 3 x eSATA (Port Multiplier) Interface for Easy Connection
- 120mm x 1 Cooling Fan for Ventilation
- LED Indicators for Power and Activity on Each HDD Tray
- Up to 15 Hot-Swappable 3.5″ Drive Trays

dAGE415U40TL-PM

4U 15-bay SAS/SATA eSATA Port Multiplier Trayless JBOD Chassis 750W PSU



Specifications

Dimension (W x H x D)	19 x 7 x 20 inches
Cooling	1 x 120mm Cooling Fan
HDD Interface	SAS/ SATA I/II
Host Interface	3 eSATA Connectors (Port Multiplier)
LED Display	LED for Power On/Off, HDD
Hot-Swap	Both on Host and Device
Material	Chassis: 1.2 mm SECC Zinc-Coated Steel
Power Supply	750W single psu (with 400W redundant psu model: dAge415U40TL-PM-R)

Features

- Supports SAS/ SATA I/II HDDs
- 3 x eSATA (Port Multiplier) Interface for Easy Connection
- 120mm x 1 Cooling Fan for Ventilation
- LED Indicators for Power and Activity on Each HDD Tray
- Trayless Design
- Up to 15 Hot-Swappable 3.5″Trayless Drive

727 Phillips Drive, City of Industry, CA 91748 | TEL:1-888-989-1189 | FAX: 1-626-301-0588 | www.istarusa.com